MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

Product Name: **BWT-140**

SECTION I - Product and Company Identification

 Patriot Industrial Technologies, Ltd.
 Phone:
 (330) 699-4429

 P.O. Box 151
 Fax:
 (330) 699-9429

 Uniontown, OH 44685
 Date:
 June 6, 2006

Emergency Telephone Number: 1-800-255-3924

SECTION II - Hazardous Ingredients/Identity Information

Hazardous Component	CAS#	OSHA PEL	ACGIH TLV	% Composition
Sodium Hydroxide	1310-73-2	2.00	2.00	3 - 8%
Sodium Sulfite	7757-83-7	N.A.	5.00	2 - 10%
Acrylic Acid Polymers	N.A.	N.A.	N.A.	2 - 10%
Sodium Lignosulfonate	68131-31-7	N.A.	N.A.	5 - 10%

SECTION III - Physical/Chemical Characteristics

Physical State: Liquid Vapor Density (AIR = 1): N.A. Vapor Pressure (mm Hg): Color: Brown N.A. Odor: None Solubility in Water: Complete **Boiling Point:** Specific Gravity (H2O): N.A. 1.08 Melting Point: Evaporation Rate: N.A. N.A.

pH over 12

SECTION IV - Fire and Explosion Hazard Data

Flash Point: > 212 F, TCC Fire Fighting Procedure: Wear self-contained breathing apparatus

Flammability Limits in Air: N.A. Unusual Fire or Explosion Hazards: None Known

Extinguishing Media: Water

SECTION V - Reactivity Data

Stability: Stable

Conditions to Avoid: Excessive heat in a confined vessel.

Materials to Avoid: Magnesium, Aluminum, Zinc

Hazardous Decomposition Byproducts: Flammable Hydrogen Gas

Hazardous Polymerization: Will not occur

SECTION VI - Health Hazard Data

Routes of entry: Inhalation: No Skin: Yes Ingestion: Yes

Health Hazards (Acute and Chronic): Causes irritation and possible permanent damage to eyes and skin. Ingestion will irritate mouth,

throat, and stomach. May cause severe allergic reaction in sulfite sensitive individuals.

Carcinogenicity: None NTP: No IARC Monographs: No OSHA Regulated: No

Signs and symptoms of exposure: May cause irritation and possible permanent damage to eyes, skin, mouth, throat, stomach, and respiratory

system.

Medical conditions aggravated by exposure: N.A.

SECTION VII - First Aid Procedures:

INGESTION – Do not induce vomiting. Contact physician immediately.

SKIN AND EYE CONTACT - Flush with water for 15 min. Contact a physician.

SECTION VIII- Accidental Release Measures

In case of Release or Spill: Contain spill for proper disposal.

This material is a hazardous waste: Corrosivity (D002)

Waste Disposal Method: Dispose of according to local, state, and federal regulations.

SECTION IX - Precautions for Safe Handling and Use

Handling and Storing: Safety goggles recommended.
Other Precautions: For industrial use only.

SECTION X - Control Measures / Personal Protection

Gloves: Rubber, plastic, or other impervious material

Respirator: NIOSH approved suggested Ventilation: Local exhaust: As required

Mechanical: Normal

Special: None Other: None

Eye Protection: Goggles
Other Protection: None
Work/Hygienic Practices: None

SECTION XI - Ecological Information - No information is available

DISCLAIMER

The information contained herein was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions for use, handling, storage and disposal of this product are beyond Patriot Industrial Technologies control, it is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense arising from the product's improper use. No warranty, expressed or implied, regarding the product described herein shall be created by or inferred from any statement or omission in this MSDS. Various government agencies (e.g., DOT, EPA, FDA) may have specific regulations concerning the transportation, handling, storage, use or disposal of this product which may not be reflected in this MSDS. The user should review these regulations to ensure full compliance.